

K-NPHWD

Quick Change Drinking Water System

neo•PURE™



Residential/Commercial Filtration Applications

Standard Features

- Manufactured in the USA (filter and head)
- NP-QCB01PB 1 micron filter for sediment, chlorine taste and odor, cysts, and lead
- Self-contained sealed cartridge reduces potential for introducing bacteria
- NP-QCB01PB cartridge is tested and certified to NSF Standard 42 and 53
- Kit includes: single filter mounting bracket with mounting screws, inline valve assembly with quick-connect fittings, NP-QCB01PB filter, 6 feet of 1/4" tubing, lead-free angle stop adapter

Also available with drinking water faucet FCT-502-CH (chrome) or FCT-502-BN (brushed nickel)

Product Specifications

Filter Media

Coconut shell carbon block with phosphate

Filter Capacity

1250 gallons for lead

Micron Rating (Nominal)

1 micron

Flow Rate

0.5 gpm

Connection Type

1/4" quick connect

Operating Temperature

35-100 °F

Operating Pressure (Maximum)

125 psi

Dimensions

13.5"H x 3.25"W x 3.5"D

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Applications:

- Drinking Water Systems



Tested and certified to NSF Standard 42 and 53. Only applies to NP-QCB01PB filter cartridge. Does not apply to K-NPQ1 system.

NeoLogic
SOLUTIONS
Filtration Division

9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008

Tel 855.896.3525 • Fax 866.409.9622

www.neologicsolutions.com • info@neologicsolutions.com

STUART, FL • BEAVERTON, OR • GREENVILLE, SC • SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives:
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

We ship six
days a week!

FedEx



2802110-00 Carbon Block Prefilter Specifications



Contaminants Reduced

Chlorine, sediment/dirt/rust, lead, cyst

Filter Media

Coconut shell carbon block

Filter Capacity

500 gallons or 6 months

Micron Rating (Nominal)

0.5 sub-micron

Flow Rate

1.0 gpm

Dimensions

10"H x 2-1/2" diameter

Connection Type

1/4" quick connect

Operating Temperature

100°F maximum

Operating Pressure (Maximum)

30-100 psi



2802140-00 Hollow Fiber Membrane Specifications

Contaminants Reduced

Bacteria, cyst, particulates, virus reduction

Filter Media

Hollow fiber membrane, polyethersulfone (PES)

Filter Capacity

1000 gallons or one year

Micron Rating (Nominal)

0.025 sub-micron

Flow Rate

1.0 gpm

Dimensions

10"H x 3-3/8" diameter

Connection Type

1/4" quick connect

Operating Temperature

100°F maximum

Operating Pressure (Maximum)

30-100 psi

Twice the flow rate

2X



Benefits of the TL3 Ultrafiltration Membrane

- The Neo-Pure TL3 **0.025 sub-micron** membrane has **twice as much surface area** when compared to other undersink ultrafiltration drinking water systems
- This added surface area allows the TL3 system to operate at a **higher flow rate of 1.0 gpm**
- This **higher flow rate** means that you can use your new TL3 ultrafiltration system to supply water to multiple points of use simultaneously, such as a drinking water faucet, refrigerator ice maker, instant hot water system, etc.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008

Tel 855.896.3525 • Fax 866.409.9622

www.neologicsolutions.com • info@neologicsolutions.com

STUART, FL • BEAVERTON, OR • GREENVILLE, SC • SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives:
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

We ship six
days a week!

