
NP-0VF001 Oasis VersaFilter Compatible Water Filter



Contaminants Reduced:



- 0 Cyst
- 0 Lead
- Sediment, Dirt and Rust







Tested and certified to NSF Standard 42 and 53

neo•pure

Residential/Commercial Filtration Applications

Standard Features

- Manufactured in the USA 0
- 0 Spun polypropylene prefilter wrap
- 0 Double o-ring seal prevents bypass
- 0 Eco-friendly coconut shell carbon block filter media
- 0 Shut-off valve engages automatically when filter is installed or removed
- 0 Cartridge is sealed, preventing the potential for introducing bacteria through handling
- Automatic shut-off inside filter head 0
- 0 Used in Oasis® Barrier-Free Versacooler II and split level models with Versafilter System PFAC, PF8AC, PF8ACEE, PF8ACSL, PRF8ACSL, PF8ACSLEE, PRF8ACSLEE, PFACSL, or PRFACSL

Product Specifications

Dimensions

2-1/2" diameter x 10"

Filter Media Coconut shell carbon block

Capacity

1250 gallons for lead, 2500 gallons for chlorine reduction

Operating Temperature 35-100°F (2-38°C)

Maximum Operating Pressure 125 psig (8.6 bar)

Maximum Flow Rate 0.5 gpm

Micron Rating (Nominal) 1 micron

Change Frequency 6 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622 www.neologicsolutions.com · info@neologicsolutions.com STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives: Mon-Fri 8a-8p, Sat 8:30a-4:30p EST



© Copyright 2014 NeoLogic Solutions. All Rights Reserved. Manufacturer reserves the right to make changes without notice.