





# **Contaminants Reduced:**

- Chlorine Taste and Odor
- Sediment

# Residential/Commercial Filtration Applications

# **Standard Features**

- Manufactured in China
- Granular activated carbon (GAC) filter
- Two-stage water filter: first stage uses a graded density prefilter; second stage passes water through granular activated carbon to reduce unwanted tastes, odors and chlorine
- Compatible with Aqua-Pure® AP217; also fits Aqua-Pure® AP200 and Purwater® PW-200
- Manufactured with FDA CFR-21 compliant materials

# **Product Specifications**

#### **Filter Media**

Granular activated carbon (GAC)

# **Micron Rating (Nominal)**

5 microns

#### **Chlorine Capacity**

2,000 gallons @ 2.0 GPM

#### **Dimensions**

3-3/8" OD x 7" (17.8 cm)

### **Operating Temperature**

40°F to 145°F (4.4°C to 62.8°C)

# **Maximum Flow Rate**

2 gpm

# **Operating Pressure**

25 to 125 psi

### **Change Frequency**

6 to 12 months

## **WARNING:**

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622

 $www.neologic solutions.com ~\cdot~ info@neologic solutions.com$ 

STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

#### **QUESTIONS?**

Ask one of our Service Representatives: Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

