SDG-45 Series 25 Micron Sediment Depth Grooved Cartridges





Contaminants Reduced:

- O Dirt
- Rust
- Sediment

Residential/Commercial Filtration Applications

Standard Features

- Manufactured in China
- Rigid construction holds up to heavy water pressure conditions
- Grooves create increased surface area for longer cartridge life and high dirt-holding capacity compared to non-grooved polypropylene filters
- Melt blown polypropylene filter media
- Porous cylinder inside the filter traps sediment, dirt and rust efficiently without affecting the water flow

BATHROOM

BASEMENT

neo-pure"

Filter

Application

KITCHEN

Product Specifications

Filter Media

Polypropylene

Micron Rating (Nominal)

25 microns

Dimensions

4-1/2" dia. x 20"

Cartridge Style

Drop-In

Operating

Temperature

100°F (37.78°C)

Pressure Rating

Up to 125 psi

Maximum Flow Rate

45 gpm

Case Pack

12 per case (10BB), 6 per case (20BB)

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.





9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622

www.neologicsolutions.com \cdot info@neologicsolutions.com

STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA

QUESTIONS?

Ask one of our Service Representatives: Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

