

K-NPDWS

Quick Change Drinking Water System



Applications:

- Drinking Water Systems



Tested and certified to NSF Standard 42 and 53. Only applies to NP-QCB01PB filter cartridge. Does not apply to K-NPQ1 system.

Residential / Commercial Filtration Applications

Standard Features

- Manufactured in USA (filter and head)
- NP-QCB01PB 1 micron filter for sediment, chlorine taste and odor, cysts, and lead
- Valve-in-head design engages automatically when the filter is installed or removed
- Self-contained sealed cartridge reduces potential for introducing bacteria
- NP-QCB01PB cartridge is tested and certified to NSF Standard 42 and 53
- Kit includes: single filter mounting bracket with mounting screws, valve-in-head assembly with quick-connect fittings, NP-QCB01PB filter, 6 feet of 1/4" tubing, lead-free angle stop adapter

Also available with drinking water faucet FCT-502-CH (chrome) or FCT-502-BN (brushed nickel)

Specifications

Filter Media

Coconut shell carbon block with phosphate

Filter Capacity

1250 gallons for lead

Micron Rating (Nominal)

1 micron

Flow Rate

0.5 gpm

Connection Type

1/4" quick connect

Operating Temperature

35-100°F

Operating Pressure (Maximum)

125 psi

Height, Width, Depth

13.5"H x 3.25"W x 3.5"D

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

DISTRIBUTED BY: