NP-OVF001 **Oasis VersaFilter Compatible Water Filter**





Contaminants Reduced:

- Lead
- Sediment, Dirt and Rust
- Cysts
- Chlorine Taste and Odor







Tested and certified to NSF Standard 42 and 53



Residential / Commercial Filtration Applications

Standard Features

- Manufactured in USA
- Spun polypropylene prefilter wrap
- Double o-ring seal prevents bypass
- Eco-friendly coconut shell carbon block filter media
- Shut-off valve engages automatically when filter is installed or removed
- Cartridge is sealed, preventing the potential for introducing bacteria through handling
- Automatic shut-off inside filter head
- Used in Oasis® Barrier-Free Versacooler II and split level models with Versafilter System PFAC, PF8AC, PF8ACEE, PF8ACSL, PRF8ACSL, PF8ACSLEE, PRF8ACSLEE, PFACSL, or PRFACSL

Specifications

Dimensions

2-1/2" diameter x 10"

Filter Media

Coconut shell carbon block

Capacity

1250 gallons for lead, 2500 gallons

for chlorine reduction

Operating Temperature 35-100°F (2-38°C)

Maximum Pressure

125 psig (8.6 bar)

Maximum Flow

0.50 gpm

Micron Rating (Nominal)

1 micron

Change Frequency

6 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



DISTRIBUTED BY: