

# NP-RFG20BB

## Radial Flow Filter Cartridge



### *Residential/Commercial Filtration Applications*

## Standard Features

- Manufactured in China
- Environmentally-friendly coconut shell granular activated carbon (GAC) filter
- Ideal for point-of-entry (POE) and other high flow rate application
- Compatible with Pentek® RFC20-BB, 155247-43, Watts® MAXRFL-FF20
- Drop-in cartridge style
- NSF 42 certified materials

## Product Specifications

### Filter Media

Coconut shell granular activated carbon (GAC)

### Micron Rating (Nominal)

25 microns

### Dimensions

4-1/2" dia. x 20"

### Capacity

40,000 gallons

### Operating Temperature

40 to 100 °F (4.4 to 37.8 °C)

### Operating Pressure

30 to 100 psi

### Maximum Flow Rate

6 gpm

### Change Frequency

6 months

### WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

## Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment



This NP-RFG20BB filter is Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only.

COMPONENT



2299 Ridge Rd., Greenville, SC 29607  
Phone 888-859-1188 • Fax 864-284-1819  
[www.neologicsolutions.com](http://www.neologicsolutions.com) • [info@neologicsolutions.com](mailto:info@neologicsolutions.com)

### QUESTIONS?

Ask one of our Service Representatives:  
Mon-Fri 8a-8p, Sat 8:30a-4:30p EST

We ship six  
days a week!

